

DAREX® GROUT FLUIDIFIER

Powder fluidifier

DESCRIPTION

DAREX® GROUT FLUIDIFIER is a ready to use dry powder admixture. DAREX® GROUT FLUIDIFIER, when added to a

conventional cement / sand mix, produces a fluid water retentive grout. DAREX® GROUT FLUIDIFIER complies with AS 2159 Piling Code.

BENEFITS

- Produces fluid grout at low water content
- Water retentive to prevent premature stiffening
- Enables set extension to maintain fluidity

APPLICATION

- Used at cement / water ; cement / sand / water ; cement / fly ash / sand / water combinations
- Conventional grouts to produce fluid and non-setting water retentive grout system
- Horizontal and vertical grouting duct work
- Grouting piling systems, post tension cables, anchor bolts, rock stabilisation
- Grouting of pre-placed aggregate

INDICATIVE INFORMATION

Product Nature	Dry powder
Color	Light brown
Lifetime	12 months

PACKAGING

- 5 kg bag

SAFETY

Prior to any use, please read carefully the Safety Data Sheet (SDS).

METHOD OF USE

Dosage :

DAREX® GROUT FLUIDIFIER is normally used at a dose rate in the range of 0.5% to 1.0% (solids/ cement). The rate for a given application depends on such factors as type and brand of cement, grout mix design, ambient temperature and setting extension required.

Note:

Allow 1 kg DAREX® GROUT FLUIDIFIER per 100 kg cement. For a normal 25 MPa cement / sand / grout which would be approximately 520 kg cement / 1,200 kg sand per cubic metre, allow 5 kg DAREX GROUT FLUIDIFIER®.

Equipment :

Please contact your local Chryso representative for further information regarding the dispensing equipment for this product.

COMPATIBILITY

- Compatible with other Chryso admixtures