TECHNICAL DATA SHEET

Chryso Concrete Solutions

07/10/2026

Chryso® CONVERT-C

Returned Concrete Treatment Admixture

DESCRIPTION

Chryso® CONVERT-C is an additive for the treatment of returned plastic concrete to convert it into a dry, hardened and granular state.

Adding Chryso® CONVERT-C directly into the mixer drum is easy, fast and efficient. After the discharge of the granular material, a standard washout procedure can be used to clean the drum.

BENEFITS

- Easy to use, packed in disintegrable bags (500 g)
- Allows for standard washout procedures of the mixer drum
- Easy discharge of newly formed aggregates with no leftover
- Produces quality road base, fill material ; also suitable for low-grade concrete mixes as a partial aggregate replacement

APPLICATION

- All cement types
- Ready mix concrete
- Paving concrete

INDICATIVE INFORMATION

Product Nature	powder
Color	Off white - beige
Lifetime	24 months
Specific gravity (kg)	0,800

PACKAGING

- Bucket

SAFETY

Prior to any use, please read carefully the Safety Data Sheet (SDS).

METHOD OF USE

- Chryso® CONVERT-C is directly added to the concrete truck
- The mix should be done at a minimum speed of 15 to 18 rotations per minute. The minimum required time to dry the concrete is between 3 and 5 minutes
- Once the concrete has been dried out, mixing should stop, and materials unloaded from the truck
- Chryso® CONVERT-C is packaged in 500g water-soluble bags, each 12 kg bucket contains 24 bags
- Refer to the Convert C usage guide for more details

Dosage :

From 1 to 2 kg / m^3 depending on the type of concrete to be treated and its water content (typically 1.5 kg / m^3). The optimum dosage should be determined based on field trials. Because local job conditions vary, please contact your local Chryso sales representative for further assistance if using the product outside the recommended dosage ranges

PRECAUTIONS

- Chryso® CONVERT-C must be stored closed, away from humidity and direct sunlight
- It should not be stored below 5°C or above 35°C

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However,it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be con ducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs.

14 Colebard Street West, Archerfield QLD 4108, Australia Tel.:AU: 1800 855 525 | NZ: 0800 552 235

chryso SAINT-GOBAIN